



## Specifications Ledvance LED Downlight Performance DN155 14W 1600lm 65D - 840 Cool White | 180mm - IP54

[View Product](#)

### General Information

|                      |                                    |
|----------------------|------------------------------------|
| SKU                  | 238963                             |
| EAN                  | 4058075459151                      |
| Manufacturer Code    | 4058075459151                      |
| Brand                | Ledvance                           |
| Manufacturer Name    | DL UGR19 DN155 PFM 14W/840 WT IP54 |
| Budgetlight warranty | 5 Years                            |
| Average Lifetime (h) | 70000                              |

### Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Emergency Lighting          | No              |
| Tiltable                    | No              |
| Technology                  | LED Integrated  |
| Wattage                     | 14W             |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 840 Cool White  |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light Colour Options        | Single Color    |

|                         |                    |
|-------------------------|--------------------|
| Inclusief Driver        | Yes                |
| Beam Angle (degree)     | 65                 |
| Luminous Flux (Lumen)   | 1600lm             |
| Lumen per watt          | 115                |
| Powerfactor             | >0.90              |
| Installation Depth (mm) | 100                |
| Unified Glare Rating    | < 19 - For offices |
| Optische Afdekking      | PC (Polycarbonate) |
| Type product            | LED Downlight      |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 155               |
| IP-rating              | IP54              |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Bedrijfstemperatuur    | -20 to +45        |
| Housing                | Aluminium         |
| Colour of the Fixture  | White             |
| Colour of material     | White             |
| Fixture Connection     | Screw terminal    |
| Product Serie          | DN155             |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 65  |
| Diameter (mm) | 180 |

## Sensor Information

Type of sensor

No Sensor

## Why Budgetlight?



Guaranteed **budget prices**



Up to **7 years warranty**



**Easy** return process



Long-life **LED solutions**