



Specifications Noxion LED Panel Delta Value V5 Backlit 28W 3920lm - 830/840 CCT | 120x30cm - UGR <19 - Dali Dimmable

[View Product](#)

## General Information

|                      |                                                                                                      |
|----------------------|------------------------------------------------------------------------------------------------------|
| SKU                  | 250652                                                                                               |
| EAN                  | 8719157052474                                                                                        |
| Manufacturer Code    | 8719157052474                                                                                        |
| Brand                | Noxion                                                                                               |
| Manufacturer Name    | Noxion LED Panel Delta Value V5 28W 3920lm 2CCT 300*1200 (Philips Driver) UGR<19 Backlit - DALI dimm |
| Budgetlight warranty | 6 Years                                                                                              |
| Average Lifetime (h) | 90000                                                                                                |
| Product Serie        | Delta Value                                                                                          |

## Technical Information

|                             |                                  |
|-----------------------------|----------------------------------|
| Technology                  | LED Integrated                   |
| Replaces (Watt)             | 2x36                             |
| Wattage                     | 28W                              |
| Voltage (V)                 | 220-240                          |
| Dimmable                    | Yes, Dali                        |
| Colour Code                 | 830 Warm White, 840 Cool White   |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White |
| Colour Rendering (Ra)       | 80-89                            |
| Colour of Light             | White                            |
| Light Colour Options        | CCT                              |

|                        |                   |
|------------------------|-------------------|
| Luminous Flux (Lumen)  | 3920lm            |
| Lumen per watt         | 140               |
| IP-rating              | IP20              |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Fixture Connection     | Push Terminal     |
| Afwerking Reflector    | Frosted           |
| Powerfactor            | >0.90             |
| Type product           | LED Panel         |

## Fixture Information

|                       |                    |
|-----------------------|--------------------|
| Mounting Method       | Recessed           |
| Unified Glare Rating  | < 19 - For offices |
| Optische Afdekking    | PS (Polystyrene)   |
| Bedrijfstemperatuur   | -20 to +40         |
| Colour of the Fixture | White              |
| Housing               | Aluminium, Metal   |
| Colour of material    | White              |

## Dimensions

|                       |          |
|-----------------------|----------|
| Afmetingen LED Paneel | 120x30cm |
| Length (mm)           | 1195     |
| Width (mm)            | 295      |
| Height (mm)           | 32       |

**Sensor Information**  Guaranteed **budget prices**  Up to **7 years warranty**

Type of sensor



**Easy** return process

No Sensor



Long-life **LED solutions**